



THE TRIMPRO ROTOR IS DESIGNED TO BE USED WITH HEAVY DUTY GARDEN PLANTS

UNPACK AND CHECK FEATURES

1. Carefully read the security instructions (see warnings) and follow using the machine.
2. Plug the machine into an electrical outlet.
3. Turn on the machine using the two ON/OFF switches.
4. Fill the upper container with freshly harvested plants without branches.
5. Set the plants more spaced in the machine for 1 to 3 minutes or until the electrical is stopped.
6. Open the roll door and reach open until the upper container empty. REPEAT steps 4 to 6 as needed.
7. Frequently remove the accumulation of plants under the machine. The accumulation should never reach the roller in order not to obstruct the roller rotation.
8. Turn off the machine using the two ON/OFF switches.
9. Keeping the machine from the electrical outlet.



BEFORE YOU CAN USE THE TRIMPRO ROTOR YOU MUST ASSEMBLE THE BLADES. READ ALL THE INSTRUCTIONS USING THE 20" GUIDE ROLLER



MAINTENANCE



In order to facilitate the cleaning, clean both sides of the guide and blade frequently with detergent diluted in a tank. This must be done when the machine is not running. Clean the blade after repeatedly using to make remove the resin from the hub. See sharpening instructions inside.

FOR INFORMATION CONTACT US TO OBTAIN

Web: www.trimpro.it • Contact: info@trimpro.it • Call (toll-free): +39-049-500-0011

Numero Verde 800-000000 (toll-free) • Assistenza Clienti 049-5000000 • Assistenza Clienti 049-5000000

WARNING: WHEN THE MACHINE IS RUNNING

- Never clean your fingers or the gloves or any other part in contact with the guide or blades.
- Safety glasses and gloves are required at all times.
- Always keep your hands dry enough so they can't get inside the guide slots.
- In case you are pregnant, avoid.
- Never walk on top of the guide.
- Do not use screws, knives or any instrument above the guide.

ADJUSTMENT OF THE BLADES HEIGHT

To adjust the height of the blades, follow the steps:

1. Completely remove the "V" screws (locking screws) from the "V" screw (locking screws). Turn the "C" screw (adjustment of the height screw). To raise the blades, turn clockwise. To lower the blades, turn counterclockwise.
2. Apply pressure on the center of the blades to be sure they are well seated on the shaft.
3. Do not tighten the "V" screw.
4. Verify the height of the blades is 20" (without including the guide). If not return to step 1.
5. For final, put back and tighten the "V" screws.
6. The "C" and the "V" screws should always be aligned with the left side of the rotor shaft (RHS). The "C" and the "V" screws should always be aligned with the left side of the rotor shaft (LHS).

CAUTION

The security screws are recommended to keep a distance of at least 18" (or less) between the guide and the blades.

ADJUSTMENT POSITION



1. Working screw (after step 10)
2. Locking screw (after step 10)
3. High adjustment screw (after step 10)

LOWER AND RAISE THE BLADE



RECOMMENDATION

1. Remove the 2 set screws located in the hole on the side of the aluminum hub (see "Installation" section).
2. Remove the blades and the hub in one piece from the motor shaft.
3. Clean the blades with detergent diluted in a tank.
4. Use a grinder to sharpen the blades.
5. Put a guide pressure using the bottom of the blades on the grooves at the sharpening angle desired.
6. Push the blades on the grooves with a movement from left to right and from right to left until each blade is properly wrapped.
7. Put back the blades and the aluminum hub on the motor shaft.
8. Put back the 2 set screws in the hole on the side of the aluminum hub. Make sure these set screws are aligned with the left side of the rotor shaft.

This safety instruction is a general recommendation. Do not perform the work if you are not qualified to do so. Always use the correct safety equipment and follow the instructions.